Dealing with indirect illumination

15-463, 15-663, 15-862
Computational Photography
Fall 2023, Lecture 18

http://graphics.cs.cmu.edu/courses/15-463

Course announcements

- Homework assignment 6 is due on Friday, December 8th.
  - Do not leave for last minute, you won't have time to complete it.
- Make-up lecture: Thursday 12/7 at 11 – 12:30 in NSH 4305.

Overview of today's lecture

- Direct and indirect illumination.
- Direct-indirect separation using high-frequency illumination.
- Back to structured light.
- Back to time-of-flight imaging.
- Direct-indirect separation using epipolar constraints.

Slide credits

These slides were directly adapted from:

- Shree Nayar (Columbia).
- Matthew O'Toole (CMU).
- Supreeth Achar (Google, formerly CMU).
- Mohit Gupta (Wisconsin).

Direct and indirect illumination

Direct and Indirect Illumination



A : Direct

B : Interreflection

C : Subsurface

D : Volumetric

Easy to separate in a renderer

full image

=



direct

+



indirect

Direct-indirect separation using high-frequency illumination

Direct and indirect components: interreflections



$$L[c,i] = L_d[c,i] + L_g[c,i]$$

radiance direct indirect

$$L_g[c,i] = \sum_P A[i,j]\, L[i,j]$$

BRDF and geometry

High Frequency Illumination Pattern



$$L^{+}[c,i] = L_d[c,i] + \alpha L_g[c,i]$$

fraction of activated source elements

High Frequency Illumination Pattern



$$L^{+}[c,i] = L_d[c,i] + \alpha L_g[c,i]$$

$$L^{-}[c,i] = (1-\alpha) L_g[c,i]$$

fraction of activated source elements

Important insight:

- Indirect illumination is approximately invariant to high-frequency lighting.
- You can think of indirect illumination effects as a low-pass filter.

High Frequency Illumination Pattern



$$L^{+}[c,i] = L_d[c,i] + \alpha L_g[c,i]$$

$$L^{-}[c,i] = (1-\alpha) L_g[c,i]$$

What does approximate invariance mean in this case?

Separation from Two Images

$\alpha = \frac{1}{2}$:

$$L_d = L_{\max} - L_{\min}, \quad L_g = 2L_{\min}$$

direct

indirect

Other Indirect Effects: Subsurface Scattering



Other Indirect Effects: Volumetric Scattering



Diffuse
Interreflections
Specular
Interreflections
Diffusion
Volumetric
Scattering
Subsurface
Scattering

Scene



Direct

Indirect

V-Grooves: Diffuse Interreflections

concave convex



Psychophysics:
Gilchrist 79, Bloj et al. 04



Direct



Indirect

Real World Examples:

Can You Guess the Images?

Eggs: Diffuse Interreflections

Direct

Indirect

Wooden Blocks: Specular Interreflections





Direct

Indirect

Kitchen Sink: Volumetric Scattering



Volumetric Scattering:
Chandrasekar 50, Ishimaru 78

Direct



Indirect

Peppers: Subsurface Scattering

Direct

Indirect

Tea Rose Leaf

Leaf Anatomy: Purves et al. 03



Direct



Indirect

Translucent Rubber Balls





Direct



Indirect

Hand

Skin: Hanrahan and Krueger 93, Uchida 96, Haro 01, Jensen et al. 01, Igarashi et al. 05, Weyrich et al. 05



Direct



Indirect

Pebbles: 3D Texture

Direct



Indirect

Pink Carnation



Spectral Bleeding: Funt et al. 91

Direct

Indirect

Mirror Ball: Failure Case





Direct



Indirect

Building Corner

Stick

Shadow

3D from Shadows:
Bouguet and Perona 99

$$L_d = L_{\max} - L_{\min}, \quad L_g = L_{\min}$$

direct

indirect

Building Corner

Direct

Indirect

Photometric Stereo using Direct Images

Shape



Application to structured light

Why is indirect illumination a problem?

Bowl on a Marble Slab



Captured images under conventional Gray codes

Issues due to indirect illumination effects

Strong Inter-reflections



Low-frequency pattern

Blurring due to
Sub-surface Scattering



High-frequency pattern

3D Visualizations: State of the Art

Errors due to interreflections



Conventional Gray (11 images)

Errors due to sub-surface scattering



Modulated Phase-Shifting (162 images)

V-Groove Scene



Conventional Gray codes

Low frequency pattern



Inverse Pattern

Pattern Edge



$I = 0.16$

Captured Image



$\bar{I} = 0.25$

Captured Image

Binarization error



Incorrect Binarization



Ground-truth Binarization

One (illuminated) Zero (not-illuminated)

Low-frequency patterns



$I = \text{Direct} + \alpha \,.\, \text{Indirect}$ $\qquad$ $\bar{I} = (1 - \alpha) \,.\, \text{Indirect}$

$\alpha \sim= 0,\ \text{Direct} < \text{Indirect} \Rightarrow I < \bar{I}$

High-frequency patterns



Pattern



Inverse Pattern



Captured Image



Captured Image

I = Direct + **0.5** Indirect > $\bar{I}$ = 0.5 Indirect

High-frequency Patterns are Decoded Correctly



Captured Image



Binary Decoding

Logical Coding and Decoding

Logical Coding and Decoding



Depth Map Comparison

Errors due to Inter-reflections



Conventional Gray Codes (11 images)



Our XOR-04 Codes (11 images)



Making the Logical XOR Codes

Conventional Gray Codes (10 patterns)

XOR of Last Pattern with Patterns 1-9 → XOR-02 Codes (10 patterns)

XOR of Second-last Pattern with Patterns 1-8 → XOR-04 Codes (10 patterns)

Ensemble of Codes for General Scenes



Conventional Gray (10 images)

Return the consistent value

Max min-



Ensemble of Codes (41 images)



XOR-04 (10 images)



XOR-02 (10 images)

Shape Comparison



Conventional Gray
(11 images)



Modulated Phase-Shifting
(162 images)



Our Technique
(41 images)

Translucent Wax Candle

Errors due to strong sub-surface scattering

Scene



Modulated Phase-Shifting (162 images)



Our Ensemble Codes (41 images)

Translucent Wax Object

Errors due to strong sub-surface scattering

Scene

Modulated Phase-Shifting (162 images)



Our Ensemble Codes (41 images)

Depth-Map Comparison

Regular Gray Codes (11 images)

Our Ensemble Codes (41 images)

Fruit Basket: Multiple Effects

Depth-maps with previous state of the art





Our Ensemble Codes (41 images)



Regular Gray (11 images)



Phase-Shifting (18 images)

Bowls and Milk: Multiple Effects





Phase-Shifting (18 images)



Modulated Phase-Shifting (162 images)



Regular Gray Codes (11 images)



Our XOR Codes (11 images)

Flower-Vase

Comparison



Phase-Shifting (18 images)



Regular Gray Code (11 images)



Modulated Phase-Shifting (162 images)

Our Ensemble Codes (41 images)

Multiple Indirect Illumination Effects

Wax Bowl



Shape Using Ensemble Codes

Multiple Indirect Illumination Effects

Deep Wax Container



Shape Using Ensemble Codes

Application to time-of-flight imaging

Interreflections and ToF Imaging





Interreflections and ToF Imaging





Interreflections Produce Incorrect Phase

Errors in Shape Recovery



camera view



Multipath Interference: Existing Work





How To Separate Different Components?

Interreflections vs. Modulation Frequency





For High Temporal Frequency
Interreflections Do Not Affect Phase

Interreflections Do Not Affect Phase

Phase Ambiguity



Unambiguous Depth Range: $R_{unambiguous} = \frac{1}{2\omega}$

Disambiguating Phase





Compute Phases at Two High Frequencies

[Jongenelen *et al.* 2010, 2011]

Micro Time-of-Flight Imaging





Modulation Signals With Micro (Small) Periods

Conventional vs. Micro ToF Imaging



Conventional ToF Shifting: One Low Frequency

Three Measurements



Micro ToF Shifting: Two High Frequencies

Four Measurements

Simulations: Cornell Box



Cornell Box: Input Images



957 MHz.



930 MHz.

Cornell Box: Phase Maps

ambiguities



957 MHz.

ambiguities



930 MHz.

0 2π

Cornell Box: Shape Comparison



Direct-Indirect Separation



$$D = 2A \quad G = O - A$$

Direct-Indirect Separation Using Three Measurements

Direct-Indirect Separation

Color Bleeding due to



Direct Component
Direct Component



Indirect Component (x2)
Indirect Component (x2)

Experimental Setup



Maximum System Modulation Frequency = 125 MHz.

Experiments: V-Groove



Scene Images Captured By PMD Sensor



apex angle = 45°



apex angle = 60°



apex angle = 90°

image resolution = 120 x 165

Reconstructed Shape using Micro ToF



Shape Comparisons

conventional ToF
mean error = 86.6 mm

Micro ToF [proposed]
mean error = 2.8 mm



How High Should The Frequency Be?



Technology (Devices) Required



Technology (Devices) Required

GHz. LED
Chen *et. al.*
1999



GHz. MSM Sensor
Buxbaum *et. al.*
2002

Material Property
(Increasing Smoothness)



Sensors/Sources
in Research Labs

Available
Off-the-Shelf

10^{3} m 10^{1} m 10^{-1} m 10^{-3} m

Geometric Scale (Decreasing Scene Size)

Technology (Devices) Required



Direct-indirect separation using epipolar probing

basic light paths



basic light paths



basic light paths



basic light paths



basic light paths



epipolar constraint & light transport



epipolar constraint & light transport



epipolar constraint & light transport



blocking epipolar paths with patterns & masks



Energy-efficient epipolar imaging

Energy-efficient transport parsing

Regular Imaging



Regular Imaging



Regular Imaging



Regular Imaging



Epipolar Imaging



Epipolar Imaging



Epipolar Imaging



Epipolar Imaging



Epipolar Imaging



Energy-efficient transport parsing



all paths

planar (mostly direct)

non-planar (always indirect)

all paths

planar (mostly direct)

non-planar (always indirect)





Benefits of Epipolar ToF Imaging



Epipolar ToF Prototype



Epipolar ToF and Global Illumination

Depth Errors (in meters)



Regular ToF @ 30MHz



Epipolar ToF @ 30MHz

Epipolar ToF and Global Illumination

Regular ToF

Epipolar ToF

Corner of Room







- Regular ToF
- Epipolar ToF

Epipolar ToF and Global Illumination

Regular ToF

Epipolar ToF



Conference Room







- Regular ToF
- Epipolar ToF

Epipolar ToF and Global Illumination

Regular ToF

Epipolar ToF

Water Fountain







- Regular ToF
- Epipolar ToF

Outdoors (Cloudy – 10 kilolux)

Scene



Regular ToF



Epipolar ToF





Outdoors (Sunny – 70 kilolux)

Scene



Regular ToF



Epipolar ToF





Outdoors (Sunny – 70 kilolux)

References

Basic reading:

- Nayar et al., “Fast separation of direct and indirect components of a scene using high frequency illumination,” SIGGRAPH 2004.
  The paper on separation of direct and indirect illumination using high-frequency illumination.
- Gupta et al., “A Practical Approach to 3D Scanning in the Presence of Interreflections, Subsurface Scattering and Defocus,” IJCV 2013.
  The paper on using XOR codes to deal with indirect illumination in structured light 3D.
- Gupta et al., “Phasor imaging: A generalization of correlation-based time-of-flight imaging,” TOG 2015.
  The paper on using high-frequency modulation to deal with interreflections and MPI in CW-ToF imaging.
- O’Toole et al., “Primal-dual coding to probe light transport,” SIGGRAPH 2012.
- O’Toole et al., “3d shape and indirect appearance by structured light transport,” CVPR 2014.
  These two papers introduce the concepts of light transport probing and epipolar probing, as well as explain how to use primal-dual coding to achieve them.
- O’Toole et al., “Homogeneous codes for energy-efficient illumination and imaging,” SIGGRAPH 2015.
  This paper shows how to efficiently implement epipolar imaging with a simple projector and camera.
- Achar et al., “Epipolar time-of-flight imaging,” SIGGRAPH 2017.
  This paper combines epipolar imaging and time-of-flight imaging.

Additional reading:

- Seitz et al., “A theory of inverse light transport,” ICCV 2005.
  This early paper shows a way to *exactly* decompose light transport by number of bounces, under certain assumptions for the imaged scene.
- Chandraker et al., “On the duality of forward and inverse light transport,” PAMI 2011.
- Reddy et al., “Frequency-space decomposition and acquisition of light transport under spatially varying illumination,” ECCV 2012.
  These two papers have additional analysis about the relationship between direct and indirect illumination and illumination frequency.
- Durand et al., “A frequency analysis of light transport,” SIGGRAPH 2005.
  This paper more formally discusses the notion of light transport frequency, and the frequency characteristics of different light transport effects (specular versus diffuse reflections, hard versus smooth shadows).